Dillon







^{*}Digital fabric cards/swatches may not be true representations of color. We recommend ordering vendor samples to ensure color correctness.

Dillon

Content: 100% Polyurethane

70% Polyester, 30% Cotton Backing:

Finish: Antimicrobial - Silver Ion Technology

Weight: 20.3 oz. per linear yard

54" Width:

Abrasion: Heavy Duty - Exceeds 200,000 Cycles

(Wyzenbeek – Cotton Duck Abradant) (ASTM D4157)

Light Fastness: Class 4/40 hrs. min. (AATCC16A)

Color Fastness: Class 5 (ASTM D3597, AATCC 8) Wet

Class 5 (ASTM D3597, AATCC 8) Dry

Physical Properties: Class 5 (ASTM D3511) Brush Pill

> 130 lbs. warp, 120lbs. weft (ASTM D 5034) Breaking Strength 61 lbs. warp, 81 lbs. weft (ASTM D 4034) Seam Slippage

50,000 Cycles (CFFA 10) Flex Resistance

Pass (CFFA 6a) Cold Crack Pass (ISO 1419) 5 weeks

Passes: California Tech. Bulletin #117 - 2013

> **UFAC Class 1** NFPA 260 Class 1 MVSS 302 Pass IMO A. 652 (16) 8.2

Cleanability: WS - Both water and solvent based solutions.

Environmental Benefit: PVC Free

> Phthalate - compliant CPSC sec. 108 Lead - compliant CPSC sec. 101

Origin: Made in China

For samples or further information, please contact:

Culp, Inc.

Contract Fabrics

1823 Eastchester Drive High Point, NC 27265 Phone: (336) 889-5161

Fax: (336) 899-7848 www.culpcontract.com